


SMD MHz Quartz Crystal Oscillator

5C-Series (5032)



Features

- 5.0 x 3.2 x H1.2±0.2 mm

Applications

- Digital Electronics, Consumer Products
- Mobile Communications
- Bluetooth, Wireless LAN



General Specifications

#	Items	Parameters
1	Frequency range	32.768kHz, 1 to 100MHz
2	Oscillation mode	Fundamental or 3rd Overtone
3	Output type	CMOS
4	Supply voltage (V _{DD})	1.8V, 2.5V, 2.8V, 3.3V, 5V
5	Operating temperature range	-20 to +70°C, -40 to +85°C
6	Storage temperature range	-55 to +125°C
7	Frequency stability vs. operating temperature range	±25ppm, ±35ppm, ±50ppm
8	Current consumption	20mA Max.
9	Duty cycle	40 to 55%, 40 to 60%
10	Rise/fall time	40ns Max. (32.768kHz), 8ns Max. (others)
11	Output level V _{OH}	0.9 x V _{DD} Min.
12	Output level V _{OL}	0.1 x V _{DD} Max.
13	Phase jitter	1.0ps Max.
14	Start-up time	10ms Max.
15	Aging at 25°C	±5ppm /year Max.

Package Dimensions, Pad Functions, & Recommended Land Pattern (Unit: mm)

