

# HUAWEI TECHNOLOGIES CO., LTD.

RECIPIENT

## SPECIFICATIONS


**MODEL :** FA-20H

**SPEC. No. :** A12-973-4B


**DATE:** Mar. 26. 2013


### SEIKO EPSON CORPORATION

8548 Naka-minowa  
Minowa-machi Kamiina-gun  
Nagano-ken  
399-4696 Japan

**CHECKED**  / TD Production Engineering Department Manager  
Kenji Komine

**CHECKED**  / TD Production Engineering Department Senior Staff  
Jun Nishide

**CHECKED**  / TD • CS Quality Assurance Department Manager  
Kazuki Matsumoto

**PREPARED**  / TD • CS Quality Assurance Department Senior Staff  
Emi Oguchi

# SPECIFICATIONS

## 1. Application

This document is applicable to the crystal unit that are delivered  
To HUAWEI TECHNOLOGIES CO., LTD. from Seiko Epson Corp.

This product complies with RoHS Directive.

This Product supplied (and any technical information furnished, if any) by Seiko Epson Corporation shall not be used for the development and manufacture of weapon of mass destruction or for other military purposes. Making available such products and technology to any third party who may use such products or technologies for the said purposes are also prohibited.

This product listed here is designed as components or parts for electronics equipment in general consumer use. We do not expect that any of these products would be incorporated or otherwise used as a component or part for the equipment, which requires an extra high reliability, such as satellite, rocket and other space systems, and medical equipment, the functional purpose of which is to keep life.

## 2. Model

The model is FA-20H.

## 3. Packing

It is subject to the packing standard of Seiko Epson Corp.

## 4. Warranty

Defective parts which originate with us are replaced free of charge in the case of defects being found with 12 months after delivery.

## 5. Amendment and/or termination

Amendment and/or termination of this specification are subject to the agreement between the two parties.

## 6. Contents

| Item No. | Item  | Page |
|----------|---|------|
| [ 1 ]    | Absolute maximum ratings                            | 2    |
| [ 2 ]    | Operating range                                     | 2    |
| [ 3 ]    | Electrical characteristics                          | 2    |
| [ 4 ]    | Environmental and mechanical characteristics        | 3    |
| [ 5 ]    | Dimensions and circuit                              | 4    |
| [ 6 ]    | Recommended soldering pattern<br>and marking layout | 5    |
| [ 7 ]    | Notes   | 6    |

### [1] Absolute maximum ratings

| No. | Parameter           | Rating value      | Note  |
|-----|---------------------|-------------------|---|
| 1   | Storage temperature | -55 °C to +125 °C | Suppose to be within CI std. at +25 °C ± 3 °C |

### [2] Operating range

| No. | Parameter             | Symbol           | Value  |      |                              |
|-----|-----------------------|------------------|--------|------|------------------------------|
|     |                       |                  | Min.   | Typ. | Max.                         |
| 1   | Operating temperature | T <sub>use</sub> | -40 °C | —    | +85 °C                       |
| 2   | Level of drive        | DL               | 10 μW  | —    | 100 μW<br>(Start up : 200μW) |

### [3] Electrical characteristics

| No. | Parameter                                    | Symbol           | Standard                      | Conditions  |
|-----|--|------------------|-------------------------------|---|
| 1   | Nominal frequency                            | f                | 25 MHz                        | Fundamental   |
| 2   | Frequency tolerance                          | f <sub>tol</sub> | $\pm 15 \times 10^{-6}$       | CL = 8 pF<br>Ta = +25 °C±3 °C<br>Drive level : 100 μW<br>Not include aging            |
| 3   | Motional resistance                          | R1               | 50 Ω Max.                     | π circuit JIS C6701<br>Drive level : 100 μW<br>Ta=-40 °C to +85 °C                    |
| 4   | Shunt capacitance                            | C0               | 5 pF Max.                     |   |
| 5   | Frequency versus temperature characteristics | f <sub>tem</sub> | $\pm 25 \times 10^{-6}$       | Ta = -40 °C to +85 °C<br>( $1 \times 10^{-6}$ at +25 °C±3 °C)<br>Drive level : 100 μW |
| 6   | Isolation resistance                         | IR               | 500 MΩ Min.                   | DC 100V × 60 sec.<br>between each terminals   |
| 7   | Frequency aging                              | f <sub>age</sub> | $\pm 3 \times 10^{-6}$ / year | Ta = +25 °C±3 °C<br>Drive level : 100 μW  |

#### [4] Environmental and mechanical characteristics

Item No.3 to No.6 shall be tested after following pre conditioning.

Pre conditioning : Test crystal must be leaving in room temperature for 2h to 24h after reflow × 3.


(The company evaluation condition : We evaluate it by the following examination item and examination condition.)

| No. | Item                         | Value *1 *2   | Test Conditions  |
|-----|------------------------------|---|--|
|     |                              | $\Delta f / f [1 \times 10^{-6}]$                   |  |
| 1   | Drop                         | $\pm 2$   | 150g dummy Jig (SE Standard) drop from 1500 mm height on the Concrete 3 directions 10 times  |
| 2   | Vibration                    | $\pm 2$   | 10Hz to 55 Hz amplitude 0.75 mm<br>55Hz to 500Hz acceleration $98 \text{ m/s}^2$<br>10Hz → 500Hz → 10Hz 15min./cycle<br>6 h (2 hours , 3 directions) |
| 3   | High temperature storage     | $\pm 2$   | +85°C × 1 000 h  |
| 4   | Low temperature storage      | $\pm 2$   | -40°C × 1 000 h  |
| 5   | Temperature cycle            | $\pm 2$   | -40°C ↔ +85°C<br>30 minutes at each temp. 100 cycle  |
| 6   | Temperature humidity storage | $\pm 2$   | +85°C × 85%RH × 1 000 h  |
| 7   | Resistance to soldering heat | $\pm 2$   | For convention reflow soldering furnace (3 times)  |
| 8   | Substrate bending            | No peeling-off at a soldered part                   | Bend width reaches 3 mm and hold for $5 \text{ s} \pm 1 \text{ s} \times 1$ time Ref. IEC 60068-2-21   |
| 9   | Shear                        | No peeling-off at a soldered part                   | 10 N press for $10 \text{ s} \pm 1 \text{ s}$<br>Ref. IEC 60068-2-21   |
| 10  | Pull – off                   | No peeling-off at a soldered part                   | 10 N press for $10 \text{ s} \pm 1 \text{ s}$<br>Ref. IEC 60068-2-21   |
| 11  | Solder ability               | Terminals must be 95% covered<br>With fresh solder. | Dip termination into solder bath at $+230 \text{ }^\circ\text{C} \pm 10 \text{ }^\circ\text{C}$ for 5 s<br>(Using Rosin Flux)                        |

< Notes >


- Item No.1 to No.11 resistance at before above tests should be less than  $\pm 20 \%$  or less than  $\pm 10\Omega$ .
- \*1 each test done independently.
- \*2 measuring 24 h later leaving in room temperature after each test.

Reflow condition (follow to IPC / JEDEC J-STD-020C)




## [5] Dimensions and Circuit

### 1) Dimension



### 2) Circuit

(Top View)



Pin

#1, #3 : X'tal

#2, #4 : GND

Type

FA-20H

Terminal treatment


Au plate

Unit


1 = 1mm

[6] Recommended soldering pattern and Marking layout

1) Recommended soldering pattern



2) Marking layout



Production month

|         |          |       |         |          |          |
|---------|----------|-------|---------|----------|----------|
| January | February | ..... | October | November | December |
| 1       | 2        | ..... | X       | Y        | Z        |

- Nominal frequency is only one example.
- Nominal frequency omits the figure below the first place of decimals.  
Ex) 25 MHz..... [250]
- The above marking layout shows only marking contents and their approximate position and it is not for font, size and exact position.


Type : FA-20H

Unit : 1 = 1mm

## [7] Notes

1. Max three (3) times re-flow is allowed. Its recommended to manually solder when not enough/no solder detected.( Using soldering iron at +350 °C Max × within 5 seconds)
2. Patterning on a board should follow our company recommended pattern.
3. Applying excessive excitation force to the crystal resonator may cause deterioration damage.
4. Start up time of oscillation may be increased or no oscillation may occur unless adequate negative resistance is allocated in the oscillation circuit In order to avoid this, please provide enough negative resistance to the circuit design.

### How to check the negative resistance



- (1) Connect the resistor(R) to the circuit in series with the crystal Resonator.
- (2) Adjust R so that oscillation can start (or stop).
- (3) Measure R when oscillation just start (or stop) in above (2).
- (4) Get the negative resistance  
 $-R=R+CI$  value.
- (5) Recommended  $-R$   
 $[-R]>CI \times 5$

5. It is recommended to do patterning to the oscillator as short as possible. Abnormal oscillation may happened if the line is too long.
6. To avoid malfunction, no pattern across or near the crystal is allowed.  
Solder paste should be less than 100 $\mu$ m thickness.
7. Few data or readings taken at user side may be different from our company's data. Confirmation of the different value is necessary before application.
8. Too much exciting shock or vibration may cause deterioration on damage.  
The product may damage depends on the condition such as a shock in assembly machinery.  
Please check your process condition in advance to minimize and maintain the shock level.
9. Condensation may occur when products are used/stored under remarkable temperature change.
10. Please refer to packing specification for the storage method and packing standard.
11. This product may be affected to ultrasonic cleaning. It is depends on the cleaning conditions (Cleaning machine type/power/time/content/position etc.). The warranty will not cover any damage due to this type of usage. Check conditions prior to use.

# TAPING SPECIFICATION

## 1. APPLICATION

This document is applicable to FA-20H

## 2. CONTENTS

| Item No. | Item                 | Page   |
|----------|----------------------|--------|
| [ 1 ]    | Taping specification | 1 to 2 |
| [ 2 ]    | Inner carton         | 3      |
| [ 3 ]    | Shipping carton      |        |
| [ 4 ]    | Marking              | 4      |
| [ 5 ]    | Quantity             |        |
| [ 6 ]    | Storage environment  |        |
| [ 7 ]    | Handling             |        |



[ 1 ] Taping specification


Subject to EIA-481 & IEC-60286

(1) Tape dimensions TE0804L

Material of the Carrier Tape : PS (Electrically conductive)

Material of the Top Tape : PET+PE

10P :  $40 \pm 0.1$




Unit: mm


(2) Reel dimensions

(a) Center material : PS


(b) Material of the Reel : PS



(3) Packing  
(a) Tape & Reel



(b) Start & End Point




| Item         |              | Empty Space   |
|--------------|--------------|---------------|
| Tape Leader  | Top Tape     | Min. 1 000 mm |
|              | Carrier Tape | Min. 100 mm   |
| Tape Trailer | Top Tape     | Min. 0 mm     |
|              | Carrier Tape | Min. 160 mm   |

(4) Peel force of the cover tape


- ① angle : cover tape during peel off and the direction of unreeling shall be 165° to 180°.
- ② peel speed : 300 mm / min.
- ③ strength : 0.1 to 1 N.

[ 2 ] Inner Carton


a) Packing to antistatic bag



b) Packing to inner carton



[ 3 ] Shipping Carton



## [ 4 ] Marking

- (1) Reel marking
  - Reel marking shall consist of :
    - 1) Parts name
    - 2) Quantity
    - 3) Manufacturing Date or symbol
    - 4) Manufacturer's Date or symbol
    - 5) Others (if necessary)
- (2) Inner carton marking
  - Same as Reel marking.
- (3) Shipping carton marking
  - Shipping carton marking shall consist of :
    - 1) Parts name
    - 2) Quantity

## [ 5 ] Quantity

- 3 000 pcs./reel

## [ 6 ] Storage environment

- (1) Before open the packing, we recommend to keep less than +30 °C and 85 %RH of Humidity, and to use it less than 6 months after delivery.
- (2) We recommend to open Package in immediately before use. After open Package, We recommend to keeps less than 6 month. No need dry air before soldering work if it is less than temperature +30 °C, 85 humidity %RH.
- (3) Not to expose the sun.
- (4) Not to storage with some erosive chemicals.
- (5) Nothing is allowed to put on the reel or carton to prevent mechanical damage.

## [ 7 ] Handling

To handle with care to prevent the damage of tape, reel and products.

ATTN : HUAWEI TECHNOLOGIES CO., LTD.

No.QDS12-172  
Mar. 26 2013  
SEIKO EPSON CORP.  
TD·CS Quality Assurance Department

## Parts Failure Rate

---

These parts failure-rate for FA-20H Series are following.

Failure rate can be calculated with high temperature test result.

The calculation procedure of Failure rate is as follows.

This Series showed no failure during our with high temperature test result of +125 °C.

$$\text{Failure rate} \leq \frac{0.917}{6.6 \times 10^4 \times 578.72}$$

$$\leq 24 \text{ fit}$$

Total operating time ;  $6.6 \times 10^4$

Acceleration factor ; 578.72

Reliability level ; 60 % (at +25 °C)